Environmental Engineering and Management Journal

January/February 2009, Vol.8, No.1, 173-181 http://omicron.ch.tuiasi.ro/EEMJ/



"Gheorghe Asachi" Technical University of lasi, Romania



ADSORPTION OF N-HEXANE VAPORS ONTO NON-FUNCTIONALIZED HYPERCROSSLINKED POLYMERS (HYPERSOL-MACRONETTM) AND ACTIVATED CARBON: EQUILIBRIUM STUDIES

Adela Marilena Buburuzan Haleța^{*}, Cezar Catrinescu, Matei Macoveanu

"Gheorghe Asachi" Technical University of Iasi, Faculty of Chemical Engineering and Environmental Protection, Department of Environmental Engineering and Management, 71 Mangeron Blvd., 700050 Iaşi, Romania

Abstract

Two non-functionalized hypercrosslinked polymeric resins type Macronet (MN 202 and MN 250) were employed to remove nhexane vapors from gas phase. A comparison of the equilibrium behavior of these hypercrosslinked resins and a bituminous granular activated carbon was made. The initial n-hexane concentration in the air stream ranged from 2100 to 4500 ppm and the adsorption temperatures were 30°C, 40°C and 50°C. The results showed that the MN 250 presents the higher adsorption capacities of n-hexane, in all studied conditions. The experimental results were fitted to the Freundlich, Langmuir and Dubinin-Raduchkevich equation isotherms, to obtain the characteristic constants of each model. The maximum adsorption capacity for nhexane, determined by using these model isotherms, decreased in the following order: MN 250 > MN 202 \ge AC 20.

Key words: VOCs, hexane, adsorption, activated carbon, hypercrosslinked polymeric resins, isotherm

^{*} Author to whom all correspondence should be addressed: e-mail: adelahaleta@ch.tuiasi.ro; haletaadela@yahoo.co.uk